

# ***42 Draft Designs***

## **Lancer EVO VIII Triple Gauge Panel Installation Instructions**

**Tools Recommended:** Phillips Head Screwdriver

1. Remove A/C and heater knobs by pulling them directly outward from the center console. Remove the two Phillips head screws located under the two outside knobs. To remove center console, evenly pry the console away from the dashboard. It is held in place with many snap-in clips.
2. Remove radio by unscrewing the 4 screws holding it to the surrounding frame. Pull the radio directly outward being careful not to yank out the factory wiring. Unplug the factory radio wiring and antenna. Now would be a good time to install Mitsubishi's radio relocation kit. Follow any instructions included with the factory kit and re-install your radio in its new location.
3. With the center console removed, install gauge panel from the back of the console. The gauge panel will only install with the notches upwards, clearing the 2 top clips that hold the console to the dash.
4. Install gauges in the panel, noticing that the bezels will overhang the front of the gauge panel and latch the panel into the console. Install gauge spin-locks or mounting brackets to fasten the gauges and panel to the center console. In many cases, the mounting U brackets may be too long to fit. If this is the case, trim mounting brackets accordingly.
5. With gauge wiring completed and tested, re-install the assembled center console and gauge panel by snapping it into place. Re-install the two Phillips head screws and re-attach A/C & heater knobs.

**Go drive and enjoy your new gauges!**

**All images and text © 42<sup>nd</sup> Draft Designs 2006, all rights reserved**