



ATF 236.15

Automatic Transmission Fluid for Mercedes Passenger Car Automatic Transmission

100% Synthetic

TYPE OF USE

High performance 100% Synthetic Fuel Economy lubricant specially engineered for Mercedes passenger cars, SUV's and light duty utility vehicles automatic transmissions for which MB-Approval 236.15 specification is required.

Especially recommended for use in all Mercedes vehicles fitted with the 7 speed automatic transmissions (since 2010) and "7G-Tronic" models, where MB 236.15 specification is required. Before use always refer to the owner manual of the vehicle.

PERFORMANCES

APPROVALS

MB-Approval 236.15

MOTUL ATF 236.15 is a 100% Synthetic Fuel Economy high technology lubricant featuring outstanding performance with regards to conventional DEXRON from GM, and MERCON from Ford, standards requirements.

MOTUL ATF 236.15 exclusive and specific formula:

- Brings fuel economy for cars fitted with automatic gearboxes by reducing epicyclical gears friction.
- Protects the numerous, compact and heavily loaded gears thanks to advance anti-wear properties.
- Extends life time duration, high shear stability at high temperature and oxidation resistance.
- Improves automatic gearboxes reaction at cold temperature.
- Provides anti-shudder performance and then avoids vibrations on engine fly wheel.
- Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag.
- Anti-wear, anti-corrosion, anti-foam.

RECOMMENDATIONS

Can be mixed with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Before use always refer to the owner manual of the vehicle.

PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM1298	0.837
Viscosity at 40°C (104°F)	ASTM D445	17.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	4.35 mm ² /s
Viscosity Index	ASTM D2270	163
Pour Point	ASTM D97	-45°C / -49°F
Flash Point	ASTM D92	192°C / 378°F