



8100 Eco-lite 5W-30



Fuel Economy Gasoline engine lubricant

100% Synthetic

TYPE OF USE

100% synthetic Fuel Economy engine oil specially formulated for recent gasoline engines, turbocharged or naturally aspirated, indirect or direct injection, designed to use engine oil with low friction and low HTHS (High Temperature High Shear) viscosity (≥ 2.9 mPa.s).

Suitable for modern gasoline engines requiring a viscosity grade 30 and fuel economy lubricant (API SN and/or ILSAC GF-5 standard).

Approved GM-dexos1[®] for GM gasoline engines requiring this approval: BUICK, CADILLAC, CHEVROLET or GMC.

Compatible with catalytic converters.

This type of oil may be unsuitable for use in some engines. Refer to the owner manual if in doubt.

PERFORMANCES

STANDARDS

API SERVICES **SN** / CF
ILSAC **GF-5**

APPROVALS

GM dexos1[®] under n° GB1D0213011

RECOMMENDATIONS

Gasoline engines: ACURA, CHRYSLER, DODGE, FORD, HONDA, HYUNDAI, INFINITI, KIA, LEXUS, MAZDA, MITSUBISHI, NISSAN, SUBARU, TOYOTA ...

The API SN standard is fully backward compatible over API SM standard and all former API standards.

API SN lubricants provide outstanding oxidation resistance, better anti-deposits protection, better engine cleanliness, anti-wear protection and enhanced performance at cold temperature for Fuel Economy savings during the whole oil life span.

Based on the API SN specification, the ILSAC GF-5 standard is even more severe especially on the energy saving criteria. The requirements on the low viscosity "Fuel Economy" side of the lubricant, but also extended drain intervals, clean pistons/rings, seals compatibility and reduced content of phosphorus for after treatment systems compatibility are enhanced. The ILSAC GF-5 specification ensures perfect engine protection when gasoline containing up to 85% Ethanol is used (E85).

GM dexos1[®] standard is suitable for the whole range of GM Gasoline engines from Model Year 2011 onwards requiring an approved dexos1 lubricant (except for service fill in Europe). Specification GM dexos1[®] is designed for use with gasoline engines and replaces GM-LL-A-025, GM 6094M and GM 4718M. GM dexos1[®] is also backward compatible for pre-2011 GM gasoline vehicles.

GM dexos1[®] standard combines very stringent requirements from international standards like API, ACEA and ILSAC, together with specific GM requirements to prove Fuel Economy benefits and engine durability.

GM has developed its dexos1[®] standard in order for the oils to provide a high thermal stability and insure an outstanding resistance at high temperatures to avoid black sludge and viscosity increase that soot, coming from combustion residues, may create.

MOTUL 8100 Eco-lite 5W-30 meets all these highly demanding requirements of performance and durability set by GM, including in particular for dexos1[®] standard, the full compatibility to biofuels use such as LPG (Liquefied Petroleum Gas), CNG (Compressed Natural Gas), and bioethanol (as available at the station), when using ethanol biofuel at a mix ratio of up to 85% (Bioethanol – E85).

Some other OEMs require for their most recent Gasoline engines an API SN and/or ILSAC GF-5 lubricant to guarantee the maximum performance and durability. Examples of MOTUL 8100 Eco-lite 5W-30 possible use for these OEMs: HONDA, SUBARU and TOYOTA gasoline engines.

MOTUL 8100 Eco-lite 5W-30 provides high lubricating properties such as wear protection and high temperature resistance for better controlled oil consumption, improves oil flow at start up for faster oil pressure build up, faster rev raisings, faster operating temperature reach and fuel economy benefits.

Environment friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

RECOMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

MOTUL 8100 Eco-lite 5W-30 can be mixed with synthetic or mineral oils.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.848
Viscosity at 40°C (104°F)	ASTM D445	67.9 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.4 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.3 mPa.s
Viscosity index	ASTM D2270	162
Pour point	ASTM D97	-39°C / -38°F
Flash point	ASTM D92	240°C / 464°F
Sulfated ash	ASTM D874	0.89% weight
TBN	ASTM D2896	8.5 mg KOH/g